

K&LOC CREENS & ENCLOSURES

TYPICAL ISOMETRICS



TYPICAL SECTIONS



8"

PROFILES

1-5/8" X 2", 4", 6", 8" Standard lengths: 24'

COMPONENTS

End Caps, Mounting Clips.

ATTACHMENT

Fasten w. #12 screws* @ 6' o.c. using mounting clips. (*Not included) ⚠ See install guide for details.

L&L_S&E_IS_RA_V1

FINISHES

Woodgrains, solid colors, naturally aged metals, special order. Custom solid color matching available (additional lead times apply).

LEAD TIME

3-6 business days + shipping (subject to change).

BIM & CAD

RVT & DWG files available, see our website for details.



info@longboardproducts.com longboardproducts.com 800 604 0343

TECHNICAL SPECIFICATIONS

PHYSICAL DATA

6063-T5 Extruded Aluminum 100% Recyclable

Warranty: Finish:15 year (standard)/20 year* (ultra) (*10 week lead time);

Aluminum: 50 year

Weight (lbs/lf): 0.93 (2"); 1.3 (4"); 1.5 (6"); 1.9 (8")

TESTING

ICC-ES Evaluation Report - Division: 05 00 00 - METALS

· Section: 05 50 00 - Metal Fabrications

LARR - Los Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

Florida Building Code - Building Florida Building Code - Residential

WUI (The Wildland-Urban Interface) - California Department of Forestry & Fire Protection Office of the State Fire Marshal Listing No. 8140-2286:0500



Fire Rating: Class A Non-Combustible by ASTM E136



Light reflectance (LRV): Up to 73.2% (Ultra White)