


# **TYPICAL ISOMETRICS**



# SINGLE POST









# **BEAM END CAP**

# **ATTACHMENT**

1x3", 1x5" - Standard Lengths: 24'

COMPONENTS

**PROFILES** 

Single Post, Double Post -Standard 24'L Beam End Cap, Post End Cap - (20pcs) Spacer Bar (1", 12'), Spacer Block (100pcs) Mounting Bracket - (100pcs)

### **FINISHES**

Woodgrains, solid colors, naturally aged metals, special order. Custom solid color matching available (additional lead times apply).

Floating System attached with Mounting Brackets, End Frame System placed in posts and supported with Spacer Blocks

Spacer Bar - comes in 12ft lengths -cut for variable heights Spacer Block - 1-1/2" spacer

RS

### BIM & CAD

RVT & DWG files available. see website for details

## LEAD TIME

3-6 business days + shipping (subject to change).



LONGBOARD

info@longboardproducts.com longboardproducts.com 800 604 0343

# **TECHNICAL SPECIFICATIONS**

### PHYSICAL DATA

6063-T5 Extruded Aluminum 100% Recyclable

Warranty: Finish:15 year (standard)/20 year\* (ultra) (\*10 week lead time);

Aluminum: 50 year

Weight (lbs/lf): 0.7 (1X3); 1.1 (1X5)

### TESTING

ICC-ES Evaluation Report - Division: 05 00 00 - METALS

• Section: 05 50 00 - Metal Fabrications

LARR - Los Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

Florida Building Code: Building Florida Building Code: Residential

WUI (The Wildland-Urban Interface) - California Department of Forestry & Fire Protection Office of the State Fire Marshall Listing No. 8140-2286:0500



Fire Rating: Class A Non-Combustible by ASTM E136 & ASTM E84



Light reflectance (LRV): 5% (Black) Up to 73.2% (Ultra White)